



## Convergence in risk assessment for SEVESO sites from ASSURANCE results to ARAMIS method

Olivier Salvi, Bruno Debray

### ► To cite this version:

Olivier Salvi, Bruno Debray. Convergence in risk assessment for SEVESO sites from ASSURANCE results to ARAMIS method. Symposium "Quantitative risikoanalyse. Quo vadis ?", Mar 2006, Tutzing, Germany. pp.56-59. ineris-00972532

**HAL Id: ineris-00972532**

**<https://hal-ineris.archives-ouvertes.fr/ineris-00972532>**

Submitted on 3 Apr 2014

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# CONVERGENCE IN RISK ASSESSMENT FOR SEVESO SITES

## from ASSURANCE results to ARAMIS method

*O. Salvi, B. Debray INERIS, France*  
olivier.salvi@ineris.fr  
<http://aramis.jrc.it>

### 1. INTRODUCTION

In the SEVESO II Directive, the objectives in terms of risk management are very clear, but the remaining question is : How to reach them ? For example, there is no harmonised definition of the scenarios that have to be considered for risk assessment. Typically, the chosen scenarios (BLEVE, total loss of containment, fire in the largest tank, explosion of the largest mass of explosive, etc.) can be different according to the specific risk analysts and according to the deterministic or risk-based approach of the country applying the Directive.

In this paper, the authors will share with you the main results of the ASSURANCE project, in which 7 European organisations performed a benchmark exercise for the risk analysis of a specific plant. ASSURANCE pointed out the need for further development that were achieved in the ARAMIS project. For this latter project, the authors will present the main results and the perspectives and how the ARAMIS results constitute a major step forward in the convergence of practices in risk assessment.

### 2. ASSURANCE PROJECT

#### **Project description**

ASSURANCE means ASSESSment of Uncertainties in Risk Analysis of Chemical Establishments. This project was a benchmark exercise on risk analysis of chemical installations to understand discrepancies between experts.

The project consisted in the comparison of the selection of scenarios, the comparison of the estimation of the consequences and finally the comparison of the estimation of the probabilities.

The project lasted 3 years from 1998 to 2001. The 9 partners from 7 different countries, representatives of the risk assessment approaches implemented in Europe.

#### **Main results**

The partners used various risk analysis techniques and arrived at quite different conclusions with respect to the selection of the scenarios, the estimation of their probabilities and the estimation of their consequences.

For example, in terms of probabilities, for a classical event which is the "Rupture of 4 inch. pipe on a distribution line", the most optimistic partner estimated a probability of occurrence at  $3.4 \cdot 10^{-8}$  per year, and the most pessimistic partner at  $2.3 \cdot 10^{-4}$  per year.

Concerning the consequences of the scenario, for a rupture in a pressurized tank, the distance to reach the end point 6200 ppm in a normal atmospheric condition, was estimated by the most optimistic partner at 0,4 km and by the most pessimistic partner at 2 km.

The last comparison concerned the iso-curves for  $10^{-5}$  / year that a person die in the vicinity of the plant because of an accident. There is a difference of about 800 m between the most optimistic and the most pessimistic partners.

### **Lessons learnt from ASSURANCE**

The ASSURANCE project has shown that there are discrepancies between the experts in the definition of scenarios considered for risk assessment. Some assumptions are different and this has a strong impact on consequence calculations. There are also discrepancies in the estimation of the probabilities of some events because there is a lack of reliable and contextual data (on failure rates, reliability...). Moreover, the project pointed out that risk curves mapping is not meaningful for local authorities and the public (consequence-based approach countries).

### **3. ARAMIS PROJECT**

#### **Project description**

The ARAMIS project built further on the conclusions of the ASSURANCE project and proposed a structured approach that reduces the discrepancies in risk assessment. The main objective is to build a methodology that improves the effectiveness of the safety reports required by the Seveso 2 directive. This method combines the benefits from risk- and consequence-based approaches. It helps operator to better demonstrate that hazards are identified and risks are controlled. Finally, it provides appropriate information to base risk-related decisions like the deliverance of permit, lands use planning and emergency planning.

The project, which lasted from 2002 to 2004, consisted in the elaboration of a methodology giving consistent rules for the identification of scenarios that take into account mitigation devices and safety management, and being recognised by a large number of risk experts from Competent Authorities and from Industry, gathered in a Review Team. The methodology produces understandable information that can be represented by maps.

In ARAMIS, the risk level of an establishment is characterised with an integrated approach where 3 independent parameters are quantified :

- the Frequency of the scenarios
- their Severity
- and the vulnerability of the environment

From the risk analysis, Major Accident Scenarios are identified and then Reference Accident Scenarios that take into account the preventive measures implemented by the operator. The severity Sref and the frequency Fref of these reference scenarios are estimated. The selection of the Reference Accident Scenarios is made possible thanks to the evaluation of the efficiency of the safety management system : both the formal aspect and the safety culture within the plant. The environment vulnerability estimation describes the sensitivity of the potential targets located in the vicinity of the SEVESO II establishments.

The outputs of the ARAMIS method are mainly represented on maps.

#### **Main results**

ARAMIS method is well structured and contains 6 major steps that are described more extensively in the main chapters of a user guide.

- Identification of major accident hazards (MIMAH)
- Identification of the safety barriers and assessment of their performances
- Evaluation of safety management efficiency to barrier reliability
- Identification of Reference Accident Scenarios (MIRAS)
- Assessment and mapping of the risk severity of reference scenarios
- Evaluation and mapping of the vulnerability of the plant surroundings

**The main results are presented in the user guide that can be downloaded at :  
<http://aramis.jrc.it>**

#### **4. CONCLUSIONS AND PERSPECTIVES**

The ARAMIS method has answered some of the difficulties related to risk assessment pointed out by the ASSURANCE project.

Three project main conclusions can be drawn up.

ARAMIS method is based on the safety barrier approach. This constitutes an alternative to the probabilistic/consequence based approaches which is well understandable by the industry as well as by the competent authorities. It is didactic and pedagogic.

The safety barrier approach is also compatible with Layer Of Protection Analysis (LOPA) method and the IEC 61508 standard, which is largely implemented in the industry.

This approach leads to constructive discussions on the level of performance of safety barriers within the plant and with the authorities.

ARAMIS is a method that takes into account the specificity of the plant, its safety management system performance and its safety culture, when other methods consider only generic data.

Beside the development of an integrated risk assessment method, ARAMIS project has achieved a tremendous exchange of practices between practitioners from more than 15 EU Member States if we consider the consortium and the review panel.

This has led to a certain convergence among countries (partners and reviewers) in the way of implementing risk assessment in the framework of the Seveso 2 directive.

The project has brought elements to fulfil the need to establish a method that is capable to assess the risk level of an installation by integrating the preventive measures implemented by the operators. Such a method is a prerequisite in order to reach the goals of the SEVESO II Directive, that are to improve the prevention linked in particular with the safety management. The application of this method results in a more consistent risk evaluation and safety management strategy in all European Countries

This reflection has continued in the European Working Group on Land Use Planning (EWGLUP) which aims at exchanging experience in risk assessment and land use planning in all Member States.

**<http://aramis.jrc.it> (The user guide can be downloaded at this web address)**

#### **Acknowledgement**

The work presented in this paper has been elaborated in the frame of the EU project ARAMIS "Accidental Risk Assessment Methodology for Industries", co-ordinated by INERIS (F) and including EC-JRC-IPSC-MAHB (I), Faculté Polytechnique de Mons (B), Universitat Politècnica de Catalunya (E), ARMINES (F), Risø National Laboratory (D), Università di Roma (I), Central Mining Institute (PL), Delft University of Technology (NL), European Process Safety Centre (UK), École des Mines de Paris (F), École des Mines de Saint Etienne (F), École des Mines d'Alès (F), Technical University of Ostrava (CZ) and Jozef Stefan Institute (Si).

The project is co-funded under the Energy, Environment and Sustainable Development Programme in the 5th Framework Programme for Science Research and Technological Development of the European Commission.

## References

- [1] Council Directive 96/82/EC of 9 December 1996 on the control of major-accident hazards involving dangerous substances, Official Journal L 010 , 14/01/1997 P. 0013 – 0033
- [2] Salvi O., Kirchsteiger C., Delvosalle C., Duijm N.J., Casal J., Goossens L., Mazzarotta B., Lebecki K., Wybo J-L., Duserre G., Londiche H. & Calzia J. 2001. ARAMIS. Accidental risk assessment methodology for industries in the framework of Seveso II directive. Paper to the Seminar on Progress in European Research on Major Hazards. Brussels 10 October 2001. Chemical Risks Directorate. Belgian Ministry of Labour. Brussels.
- [3] B.Debray and O.Salvi, ARAMIS project : an integrated risk assessment methodology that answers the needs of various stakeholders, Safety and Security Engineering, WIT press, Southampton, Boston, USA, 2005, p.265-276
- [4] C. Kirchsteiger, On the use of probabilistic and deterministic methods in risk analysis, Journal of Loss Prevention in the Process Industries 12 (1999) 399–419
- [5] Bellamy, L. J. et al, 1999, IRISK, development of an integrated technical and *management risk control and monitoring methodology for managing on-site and off-site risks*, EC contract report ENV4-CT96-0243 (D612-D)
- [6] Kurt Lauridsen, Igor Kozine, Frank Markert, Aniello Amendola, Michalis Christou, Monica Fiori, Assessment of Uncertainties in Risk Analysis of Chemical Establishments The ASSURANCE project Final summary report, Risø National Laboratory, Roskilde, Denmark May 2002 52 p. <http://www.risoe.dk/rispubl/sys/syspdf/ris-r-1344.pdf>
- [7] User guide, ARAMIS Project - 5<sup>th</sup> Framework Program of the European Community, Energy, Environment and Sustainable development, Contract number : EVG1 – CT – 2001 – 00036, december 2004, 108p. available on <http://aramis.jrc.it>